OTW - VersaHone (V)



PRODUCT SHEET

"Highly Versatile"

The **OTW VersaHone Vertical** honing machines provide the flexibility, value, and ease of use ideal for those who process a broad range of parts.

[Standard Features]

- Programmable Automatic Tool Expansion System
- Precision Handwheel Control
- Profile Linear Ways
- Touchscreen PLC Operator Controls
- Part Program Storage
- Full Servo Control
- Ball Screw Reciprocation

[Options]

- IIoT Ready w/ Full Data Capability
- Remote Connectivity for Online Support and Monitoring
- Single or Multi-Spindle Configurations
- Universal Fixture or Indexing Table
- Coolant Filtration System







Capacities/Technical Specifications

OTW- VersaHone Vertical	
-------------------------	--

I.D. Capacity	0.25" – 6.0" (6.35 - 152 mm)
O.D. Capacity	8.0" (200 mm)
Stroke Capacities	12.0" (305 mm) 24.0" (610 mm) 36.0" (915 mm)
Stroke Power	5.5 kW
Spindle Drive	Up to 10 kW *
Spindle Speeds	Packages from 10 - 3500 RPM Infinitely Variable
Stroke Rate	5-90 FPM (1,5-27,4 M/MIN) Infinitely Variable

Turnkey Solutions

Please ask about OTW's complete line of tooling, abrasives & consumables.



^{*} Subject to specific application bore condition and base capacity ** Additional voltages available

480V / 3PH / 60 Hz **

Electrical System

